

PRODUCT: PTFE THREAD SEAL TAPE

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufacturer:

LAKE CITY INDUSTRIAL PRODUCTS CO.

10490 W. LAKE ROAD

LAKE CITY, PA 16423

Emergency Phone No: (814) 774-2687

Information Calls: (814) 774-2687

Product Synonym: FSH 8030-00-889-3535: FSN 8030-00-989.-3S34 Contract #: 6S-IOF-52661

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients Percentage: None

Other Ingredients:	CAS	%
Polytetrafluoroethylene	9002-84-0	100

Odorless, white solid tape. As sold this product present no know health hazards. At temperatures above 535° F the polymer will break down and the fumes could cause a temporary flu-like illness. No smoking while handling this product.

SECTION 3: HAZARD IDENTIFICATION

POTENTIAL HEALTH EFFECTS:

EYE: No harmful effects anticipated for product as sold.

SKIN CONTACT: No harmful effects anticipated for product as sold.

SKIN ABSORPTION: Skin absorption is unlikely do to the physical properties of the product.

INGESTION: No harmful effects anticipated for product as sold.

INHALATION: Inhalation is unlikely do to the physical properties of the product.

CHRONIC EFFECTS/CARCINOGENICITY:

PTFE is not listed by IARC, NTP, OSHA, or ACGIH as a carcinogen. No significate effect anticipated. Repeated oral doses of polymer resin yield non-toxic effects except for alteration in the number of circulating white blood cells after long-term dosing. Test demonstrated not developmental toxicity in animals and no genetic damage in animals or in bacterial cell cultures.

SECTION 4: FIRST AID MEASURES

INHALATION: Unlike route of entry for product sold. If exposed to fumes from overheating or combustion, move to fresh air. Consult of physician if symptoms persist.

SKIN CONTACT: This product is not likely to be hazardous by skin contact, but if redness or itching develops, then cleansing the skin with water is advisable.

EYE: Unlikely route of entry for product as sold. If mechanical irritation occurs, flush eyes with plenty of water. Consult a physician if symptoms persist.

SSP Material Safety Data Sheet

INGESTION: Unlikely route of entry for product as sold. Consult a physician if necessary.

NOTE TO PHYSICIAN: Inhaling fumes of decomposition products can induce temporary influenza-like symptoms which are describe as polymer fume fever. These symptoms include fever, cough and malaise.

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT: Does not flash

METHOD: Open cup

AUTOIGNITION TEMPERATURE: Not available

FLAMMABILITY LIMITS: Not Applicable

EXTINGUISHING MEDIA: Water, foam, dry chemical, or CO₂.

FIRE AND EXPLOSION HAZARDS: PTFE will burn in an atmosphere of 95% Oxygen when an ignition source is present. Hazardous gases/vapors product in a fire are hydrogen fluoride (HF) carbonyl fluoride, perfluoroolefins, carbon monoxide, and low molecular weight fluorocarbons.

FIRE EXTINGUISHING EQUIPMENT: Wear self-containing breathing apparatus. Wear full protective equipment. Protect from hydrogen fluoride fumes which react with water to form hydrofluoric acid. Wear neoprene glove when handling refuse from a fire involving PTFE.

SECTION 6: ACCIDENTAL RELEASE MEASURE

Sweep to avoid slipping hazard.

SECTION 7: HANDLING AND STORAGE

Enforce not smoking rules in areas where PTFE is handled and stored. Wash hands and face after handling to avoid transfer of PTFE onto cigarettes and tobacco.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

No special personal protection or exposure controls are indicated for this product as sold except those mentioned in section 5.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Melting Point: 648°F
Water Solubility: Insoluble
Odor: None
Appearance: White solid tape
Specific Gravity: Greater than 1.2

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable at normal temperature and storage conditions
Hazardous Polymerization: Will not occur
Incompatibility: Reacts with molten alkali metals and interhalogen compounds
Hazardous Decomposition Products: Above 535°F this product may evolve toxic gaseous material such as hydrogen fluoride (HF) carbonyl fluoride, perfluoroolefins, carbon

SSP Material Safety Data Sheet

monoxide and low molecular weight fluorocarbons. Particulate matter evolved from overheating may cause polymer fume fever.

OTHER INFORMATION: No shelf life. The federal government has established a three year inspection test date.

Waste disposal: Discarded product is not a hazardous waste under RCRA, 40 CFR 261. Preferred options for disposal are recycling and landfill. Incinerate only in an incinerator capable of scrubbing out hydrogen fluoride or other acidic combustion products. Treatment, storage, transportation, and disposal must be in accordance with applicable Federal, state and local regulation.

DOT: Not regulated TSCA Inventory: Listed

SARA313/302: Not listed 311/312: Not hazardous Pennsylvania: Hazardous Substance List

References: Supplier MSDA

(This information is given in good faith, but no warranty, expressed or implied is made.)